


## 0530 Premium cloth tape



### Construction:

Tape grade:	Matt cloth tape (gaffers tape)
Mesh:	80 mesh
Carrier:	65 % Polyester + 35 % Cotton
Adhesive:	Natural rubber based

### Test report:

Total thickness (micron)	: 300
Peel adhesion (gf/25 mm/180°)	: 1,050
Tensile strength (kgf/25 mm)	: 15
Elongation (%)	: 12
Ball tack (ball No.)	: 22
Holding power (mm/Hr)	
* 1 kg loading on SUS plate, 25 mm x 25 mm	: 0.5
Unwinding force (gf/25 mm)	: 800
Heat resistance (°C/min)	: 85/180
Weather resistance (Hrs)	: 8
Delamination	: No

**Above test was performed on the condition of 23±2 °C and humidity of 65±5 % (JIS Z 0237, 1254)**

### Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.