

023 MASKING TAPE 60 °C

Tape structure:

Backing: Saturated crepe paper

Adhesive: Solvent borne rubber resin

Product Description:

023 medium adhesion masking tape characterized by a semi crepe paper backing and a solvent borne rubber resin adhesive. Universal and versatile, it is suitable for professional applications in Painting and Building industry, for masking and painting operations, and for light non – critical spray painting activities at moderate high temperature.

Features:

- Medium adhesion
- Excellent holding power
- Good contact on multiple surfaces
- Good paint anchorage
- Temperature resistance 60 °C for up to 1 hour
- Indoor removal time: 5 Days

Technical information:

Properties	Units	Specification	Test method
Total weight	g/mm ²	90	ISO 536
Total thickness	mm	0.12	Internal
Peel adhesion	N/cm	2.1	AFERA 5001/PSTC 101
Tensile strength	N/cm	38	AFERA 5004/PSTC 131
Elongation at break	%	7	AFERA 5004/PSTC 131
Temperature resistance	°C	up to +60 (1 hour)	

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.



Main Application:

- Professional masking, painting and building operations (no UV exposure recommended)
- Non – critical spray painting operations at medium-high temperature
- Non – critical bundling, splicing and holding
- Temporary labeling and marking activities