

0253350 PVC masking tape Orange



Description:

0253350 construction tape is based on a specially release-treated soft PVC film coated on one-side with aggressive rubber adhesive. Extremely low unwinding force, conformable and pliable backing, makes 0253350 a good choice on construction-related works.

Application:

Used for sheltering on painting and plaster working. Also for repairing, marking, protection and maintenance.

Technical Details:	Properties	Unit	Data
	Total Thickness	mm	0.125 +/- 10 %
	Tensile Strength	kg/25 mm	4 ↑
	Elongation	%	100 ↑
	Adhesion to Steel	kg/25 mm	0.20 ↑
	Unwinding force	g/25 mm	200 ±100

Color: Orange

Shelf Life: 12 months when stored in original carton at 23 °C and 65 % R.H.

Availability: Standard 50 mm x 33 m rolls, 77 mm i.d. core.

Remark: Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.