

028 Perfect Edge Masking tape



Main applications:

building, DIY, Marina industry

Technical features:

fine lines, UV resistance, water resistance, no residual

Strengths:

- Precise paint edges
- No residue
- Multiple surfaces
- Compatible with water and solvent base paints
- Removal without breaking and easy to use

Technical information:

Properties	Spec.	Test
Total weight	82 g/m ²	ISO 536
Total thickness	92 micron	Internal
Tensile strength	30 N/cm	AFERA 5004
Elongation at break	3.5%	AFERA 5004
Adhesion to steel plate	1.4 N/cm	AFERA 5001
Removal without residue (not painted)	3 months outdoor 6 months indoor	

Available colors:

yellow

Shelf life:

12 months when stored in original carton at 23 °C and max. 50 % relative humidity.

Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.