





Description:

0171519 tape is a hand tearable, non-woven polyester fleece, halogen-free flame resistance and single coated with a pressure sensitive acrylic-based adhesive.

Application:

Specially designed for sophisticated applications in the interior of a car. With its resistance and soft backing, the product is suitable for wrapping of automotive electrical wiring harnesses to reduce the noise and anti-vibration properties.

lec	hnical	Detai	ls:

Properties	Unit	Typical Data	Notes
Total thickness:	mm	0.3 +/-0.05	
Noise damping:	dB(A)	Class C >5-≤10	acc.to VW60360
Temperature resistance	e: °C	-40- +105	
Abrasion resistance:		Class B 100-499	acc.to VW60360
Adhesion to steel:	N/cm	>1.5	
Adhesion to backing:	N/cm	>1.5	
Elongation at break:	%	≥15	
Tensile strength:	N/cm	≥20	
Unwinding force:	N/roll	4–10	

Color: Black

Test Method: ASTM D-1000

Shelf Life: 12 months when stored in original carton at 23 °C and 65 % R.H.

Availability: 19 mm x 15 m

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.

iune 2024 www.folsen.eu