

# 024 YELLOW EMBOSSED PVC MASKING TAPE

## Tape structure:

**Backing:** Soft PVC film

**Adhesive:** Solvent borne rubber resin

## Product Description:

024 construction tape is based on a on embossed vinyl backing coated on one-side with aggressive rubber adhesive. Easy tearing, low unwinding force and conformable and pliable backing, makes 024 a good choice on construction related works, both in masking and plastering.



## Features:

- Easy tearable by hand
- Low unwinding force for easy handling
- Good initial tack and reliable adhesion
- UV resistant for 14 days

## Main Application:

- Used for sheltering on painting and plaster working. Also for repairing, marking, protection and maintenance

## Technical information:

Properties	Units	Specification	Tolerance
Total thickness	mm	0.15	+/- 10%
Peel adhesion	N/cm	1.2	
Tensile strength	N/cm	11.8	
Elongation at break	%	90	

## Color:



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.