





Tape structure:

Backing: high crepe paper

Adhesive: synthetic rubber / resins clear adhesive

Characteristics:

High elongation tape mostly used in DIY for simple masking jobs, especially designed to mask curved surfaces. It is also used for sealing industrial paper before stiching.

Application fields:

building, DIY, industrial

Technical features:

painting, multiple surfaces, easy tear, round-shaped masking

Strengths:

- · High elasticity and stretch
- Highly adaptable to irregular surfaces and curves
- Compatible with solvent and water base paints
- · Removal without breaking
- 3 days indoor clear removal
- · Easy to use and unwind

Technical information:

Properties	Spec.	Test Method
Total Weight	115 g/m²	ISO 536
Total Thickness	280 µm	internal
MD Tensile strength	> 22 N/cm	AFERA 5004
MD Elongation at break	> 27 %	AFERA 5004
Adhesion to steel plate	> 0.8 N/cm	AFERA 5001
Adhesion to steel plate (strechted)	> 4.1 N/cm	

Available colour:

yellow

Storage details:

- We recommend a storage temperature between 15 and 25 °C
- The product should not be directly exposed to heat or humidity
- The product should be conditioned to room temperature before use

Shelf life:

Remark:

12 months when stored in original carton at 23 °C and max. 50 % relative humidity Above figures are for reference and cannot be treated as warranties. Customers are

advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.

march 2023 www.folsen.eu