

# 03010 DOUBLE-SIDED PE FOAM MOUNTING TAPE

## Tape structure:

**Backing:** PE foam

**Adhesive:** Acrylic solvent

**Release liner:** Glassline paper

## Product Description:

Cross-Linked Polyethylene (PE) foam is coated with high tack acrylic adhesive on both sides. Widely used in automotive industry and for home decor.

## Features:

- High initial tack and perfect conformability on various surfaces
- Completely suitable for outdoor use, resistant to UV rays, moisture and aging
- Withstands a wide range of temperature variations

## Technical information:

Properties	Units	Specification	Test method
Total thickness (without liner)	mm	1.0	Internal
Peel adhesion	N/cm	12	AFERA 5001
Holding power	hours	50	Internal
Initial tack (steel ball) 14#:	N/cm	12	Internal
Elongation	%	180	
Temperature resistance	°C	-20 - +80	



## Main Application:

- For furniture, mirrors, functional trim and decorative panels etc.
- Excellent dimensional stability for die-cutting

**Color:**



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.