

0308 DOUBLE-SIDED PE FOAM MOUNTING TAPE

Tape structure:

Backing: PE foam

Adhesive: Acrylic solvent Release liner: PE liner

Product Description:

0308 consists of 1.0 mm PE foam coated on both side with an acrylic-base pressure sensitive adhesive, protect with a blue PE film of rele ase liner. It has provided good holding power strength, long-aging ability, and suitable weatherability characteristics.

Features:

- Excellent holding power
- · Long-aging ability
- · Weather resistance



Main Application:

 Designed for mounting automobile moldings and rearview mirrors, as well as for other outdoor and DIY works.

Technical information:

Properties	Units	Specification	Test method
Total thickness (without liner)	mm	1.0	Internal
Peel adhesion	N/cm	12	AFERA 5001/PSTC 101
Holding power	hours	500	Internal
Elongation	%	300	Internal
Working temperature	%	-20 - +80	

Color:





SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.

Page 1 of 1 last update 19.05.2025