

031038 DOUBLE-SIDED PP TAPE

Tape structure:

Backing: PP film

Adhesive: Acrylic solvent

Release liner: Glassline paper

Product Description:

Transparent Polypropylene film is coated with high tack acrylic adhesive on both sides. The tape can be used for splicing, mounting and joining purposes.

Features:

- Excellent adhesion to all surfaces
- Hand tearable

Main Application:

- Excellent for bonding and mounting on even or rough surfaces in DIY projects and craft applications

Technical information:

| Properties | Units | Specification | Test method |
|---------------------------------|-------|---------------|---------------------|
| Total thickness (without liner) | mm | 0.110 | Internal |
| Peel adhesion | N/cm | 6.8 | AFERA 5001/PSTC 101 |
| Initial Tack (steel ball) 14# | mm | 120 | Internal |
| Holding power | min | 800 | Internal |

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.

