

033501 DOUBLE-SIDED TISSUE TAPE

Tape structure:

Backing: Non-woven tissue paper from cellulose fibers

Adhesive: Acrylic solvent

Release liner: Silicone and PE coating

Product Description:

Paper tissue is coated with strong acrylic adhesive on both sides. Bonds well to most surfaces and materials. Excellent for splicing and attaching applications.

Features:

- Excellent durability and adhesion to many surfaces
- For bonding different kinds of rubber, foam and fabrics
- Suitable for hand application or laminating equipment
- Very high temperature resistance

Technical information:

Properties	Units	Specification	Test method
Total thickness (without liner)	mm	0.14	Internal
Peel adhesion	N/cm	8	AFERA 5001/PSTC 101
Holding power	hours	24	Internal
Initial tack (steel ball) 14#:	mm	100	Internal
Temperature resistance 80°C	min	30	
Temperature resistance 180°C	min	3	
Working temperature	°C	+10 - +40	

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.



Main Application:

- It is perfect for general usage., such as plastic and metal details repairing, foam lamination, shoes and cloth repair, and also for paper splicing.