

04217, 04218 PACKAGING TAPE

Tape structure:

Backing: BOPP

Adhesive: synthetic rubber

Product Description:

Self-adhesive tape with BOPP backing and synthetic rubber adhesive base. This tape is suited for use on hand dispensers and automatic sealing machines. The adhesion and elasticity characteristics, together with the brilliance and transparency, typical of Polypropylene films, make it ideal for all applications in the packaging sector.

Features:

- Excellent adhesion even in recycled cartons
- Good tack
- The adhesive high holding power value guarantees a long lasting adhesion and a safe storage even with temperature variations

Technical information:

Properties	Units	Specification	Test method
Backing thickness	mm	0.025	Internal
Total thickness	mm	0.041	Internal
Peel adhesion	N/cm	5.2	AFERA 5001/PSTC 101
Tensile strength	N/cm	38	AFERA 5004/PSTC 131
Elongation at break	%	150	AFERA 5004/PSTC 131
Application temperature	°C	+6 to +45	
Temperature resistance	°C	-10 to +60	

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.



Main Application:

Designed for carton sealing and general packaging applications, for excellent holding power and consistent performance under various temperature conditions.