

044 PAPER PACKAGING TAPE

Tape structure:

Backing: Crepe paper

Adhesive: Natural rubber

Product Description:

Eco-friendly Carton Sealing Paper packaging tape with a natural rubber resin adhesive designed to seal cartons and light weight boxes. Easy to unwind and hand tearable, it provides a good hold on the application surface, even in warm environments. 50% of the raw materials contained in this tape come from natural resources. Thanks to its special adhesive formulation, this tape can be disposed together with the packaging on which it is applied without affecting the paper and cardboard recycling process, in accordance with INGEDE certification..



Features:

- Medium adhesion
- Good tack on cardboard
- Long lasting adhesion
- Recycling-friendly tape according to INGEDE Method 12

Main Application:

- Light duty carton sealing
- Manual packaging
- Non - critical bundling, splicing and holding

Technical information:

Properties	Units	Specification	Test method
Total weight	g/m ²	89	Iso 536
Total thickness	mm	0.12	Internal
Peel adhesion	N/cm	2.4	AFERA 5001
Tensile strength	N/cm	35	AFERA 5004
Elongation at break	%	7	AFERA 5004

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.