

# 048 FILAMENT TAPE CROSS-WEAVED

## Tape structure:

**Backing:** BOPP cross weave fiberglass filament reinforced

**Adhesive:** Synthetic rubber

## Product Description:

Bi-oriented polypropylene tape reinforced with crosswave glass fiber able to give a high resistance to breaking loads. Recommended for pallet packing and for high level reinforcements, it is able to allow the maximum loads safety.

## Features:

- High adhesion and excellent holding power
- Easy bonding to variety of surfaces
- Excellent tensile strength
- High resistance to nicks, abrasion and moisture

## Main Application:

Widely used in industrial bundling, reinforcing, splicing applications and for medium – heavy loads securing.



## Technical information:

Properties	Units	Specification	Test method
Backing thickness	mm	0.025	Internal
Total thickness	mm	0.135	Internal
Peel adhesion	N/cm	10	AFERA 5001/PSTC 101
Tensile strength	N/cm	240	AFERA 5004/PSTC 131
Elongation at break	%	5	AFERA 5004/PSTC 131

## Color:



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.