

## 048 Filament tape cross-weaved



### Description:

Bi-oriented polypropylene tape reinforced with crosswave glass fiber able to give a high resistance to breaking loads. Recommended for pallet packing and for high level reinforcements, it is able to allow the maximum loads safety.

### Advantages and benefits:

- Excellent adhesion to all surfaces
- Excellent tack
- High tensile strength

### Construction:

Backing: Cross Weave fiberglass filament reinforced BOPP

Adhesive: Synthetic rubber and hydrocarbon resins

Color: Clear

### Technical Details:

Properties	Unit	Spec.
Backing thickness	µm	25
Total Thickness	µm	120
Peel Adhesion	N/cm	10
Tensile Strength	N/cm	240
Elongation at break	%	5

### Shelf life:

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

### Availability:

50 mm x 50 m, 50 mm x 330 m

### Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.