

# 0510 DUCT TAPE

## Tape structure:

**Backing:** PE laminated synthetic cloth

**Adhesive:** Synthetic rubber resin - solvent free

## Product Description:

0510 PE laminated synthetic cloth duct tape, coated with synthetic rubber – resin solvent free adhesive. Characterized by excellent conformability and tensile strength, it is designed for general-purpose use, making it suitable for a variety of DIY and contractor applications. It offers good adhesive strength, durability, and flexibility. It is also resistant to moisture and can adhere well to a variety of surfaces, enabling this tape to become a perfect value for money and reliable and versatile duct tape. UV exposure not recommended.

## Features:

- Easy tear
- Excellent adhesion on PE
- Low temperature resistance
- Excellent conformability
- Suitable for multiple surfaces
- Perfectly waterproof

## Technical information:

Properties	Units	Specification	Test method
Total thickness	mm	0.155	Internal
Peel adhesion	N/cm	9	AFERA 5001/PSTC 101
Tensile strength	N/cm	35	AFERA 5004/PSTC 131
Elongation at break	%	20	AFERA 5004/PSTC 131
Temperature resistance	°C	-10 to +60	



## Main Application:

- Bundling, sealing, temporary repairing operations
- Double glazing unit sealing
- General repair and protection in construction sites
- Jointing and sealing asbestos abatement and agriculture

## Color:



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.