

## 05156 PVC duct tape



### Description:

05156 is based on a premium grade plasticized polyvinyl chloride (PVC) film, coated with an aggressive rubber resin adhesive with good aging characteristics. Designed to be highly conformable and unaffected by moisture and most chemicals. Watertight, moisture resistant, good adhesion to wood, plastic, cardboard, metals and other surfaces.

### Application:

Most suitable for duct sealing, reinforcing, mending and other applications.

### Technical Details:

Properties	Unit	Spec.
Total Thickness	mm	0.120 ± 10 %
Adhesion to Steel	kgf/25 mm	> 0.35
Tensile Strength	kgf/25 mm	> 5.0
Elongation	%	> 100
Unwind Force	kgf/25 mm	< 800

**Color:** grey

**Test Method:** ASTM D-1000

**Shelf Life:** 12 months when stored in original carton at 23 °C and 65 % relative humidity.

**Availability:** 48 mm x 30 m

**Remark:** Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.