

05164 EXTRA STRONG PVC DUCT TAPE

Tape structure:

Backing: Plasticized PVC film

Adhesive: Natural rubber adhesive

Product Description:

05164 tape consists of a 0.13 mm PVC film coated with a rubber-resin adhesive. It remains flexible across a wide temperature range and offers excellent corrosion resistance, high puncture strength, and outstanding electrical insulation properties. Designed for superior conformability, it is resistant to moisture and most chemicals. The adhesive provides strong bonding to a variety of surfaces, including wood, plastic, cardboard, metals, and more.



Features:

- Excellent corrosion resistance
- High puncture and abrasion resistance
- Excellent protective barrier
- Moisture and chemical resistance
- High conformability

Main Application:

Most suitable for a corrosion and abrasion protection on underground or above ground metal pipelines, fittings, joints and electrical conduits, etc.

Technical information:

Properties	Units	Specification
Total thickness	mm	0.15
Peel adhesion	N/cm	1.6
Tensile strength	N/cm	23.5
Elongation at break	%	100
Unwinding force	kg/25 mm	400

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.