

065 Repair tape



Description:

- Ideal for splicing and reparation of greenhouses
- UV resistance for up to 12 months
- Excellent moisture barrier

Composition:

Backing: PE

Adhesive: acrylic, water-based

Color: transparent

Technical Details:

Properties	Unit	Spec.	Tolerance
Backing thickness	µm	130	±3%
Total Thickness	µm	160	±6%
Adhesion to steel plate	gr/cm	270	±10%
Tensile Strength	kg/cm	3,2	±10%
Elongation	%	400	±10%

Storage details:

- We recommend a storage temperature between 18 and 30 °C
- The product should not be directly exposed to heat or humidity
- The product should be conditioned to room temperature before use

Availability:

50 mm x 33 m, 50 mm x 10 m, 75 mm x 10 m

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.