

067/066 Warning tape



Description:

Plasticized polyvinyl chloride (PVC) film, coated with non thermo-setting rubber based adhesive. Featured with excellent adhesion, excellent conformability, high elongation and good aging characteristics.

Application:

For use as floor/aisle marking identification and decoration.

Technical Details:

Properties	Unit	Data
Total Thickness	mm	0.15 ± 0.01
Adhesion to steel	N/25mm	3↑
Initial Tack	14 #/cm	8.0 ↓
Tensile Strength	N/25mm	40 ↑
Elongation at break	%	130

Color: Yellow/black, red/white

Test Method: GB/T

Shelf Life: 12 months when stored in original carton at 23 °C and 65 % R.H.

Size: 50 mm x 33 m

Remark: Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.