

# **069 ANTI-SLIP TAPE**

### Tape structure:

Backing: PVC film with transparent quartz sand

Adhesive: Solvent acrylic adhesive

Liner: Silicone paper

## **Product Description:**

Anti-slip tape is a safety product designed to provide enhanced traction on slippery surfaces, reducing the risk of slips and falls. It features a durable, abrasive surface bonded to a pressure-sensitive adhesive for easy application on a variety of substrates. Ideal for use in industrial, commercial, and residential settings, it ensures reliable performance even in high-traffic areas.



## **Features:**

- High traction surface with durable abrasive material to provide excellent grip and reduce slip hazards.
- Strong adhesion with pressure-sensitive adhesive for quick, secure bonding to most clean, dry surfaces.
- · Weather resistant for indoor and outdoor use

# **Main Application:**

Anti-slip tape is commonly used on stairs, ramps, walkways, ladders, and other potentially slippery surfaces in industrial, commercial, and residential environments to enhance safety and prevent accidents.

## **Technical information:**

Properties	Units	Specification	Test method
Total thickness (without liner)	mm	0.90	Internal
Peel adhesion	N/cm	4.8	GB/T2792-1998
Tensile strength	N/cm	24	GB/T7753-1987
Initial tack (ball 8#)	cm	4	GB/T4852-2002
Elongation at break	%	25	GB/T7753-1987
Friction force	R13	>0.70	
Service temperature	°C	-20 - +80	

## Color:





## **SHELF LIFE AND STORAGE**

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.

Page 1 of 1 last update 14.07.2025