

0695005 Anti-Slip tape



Description:

Folsen Anti-slip Tape can be used indoors or outdoors and is easily installed to any clean, dry and oil-free surface, including wood, metal and concrete – just peel off the paper backing and press in place – it's ready immediately.

Construction:

Aluminium oxide, silicon carbide

Carrier: PVC

Adhesive: Solvent acrylic adhesive Liner: Silicon paper white

Surface: 80 grit

Technical Details:

Adhesion to steel: $1500 \text{ g} / 25 \text{ mm} \uparrow$ Tensile strength: $6.0 \text{ kg} / 25 \text{ mm} \uparrow$

Elongation at break: 25 % ↑

Thickness: $0.8 \pm 0.2 \text{ mm}$ Service temperature range: $-25 \,^{\circ}\text{C}$ to $80 \,^{\circ}\text{C}$

Resistance to water: Good
Ageing resistance Excellent

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.

may 2019 www.folsen.eu