

# 0733 ACRYLIC FOAM TAPE

## Tape structure:

**Backing:** Acrylic foam

**Adhesive:** Acrylic solvent

**Release liner:** MOPP film

## Product Description:

0733 is clear acrylic tape. Due to it's colorless tape is ideal for bonding transparent materials or for applications where a colored bond line is unacceptable.



## Features:

- Good resistance to moisture and plasticizer
- Very good Ultra violet light resistant
- Resistance to abrasion, corrosion and moisture
- Suitable for indoor and outdoor environments
- Clean and easy to use

## Main Application:

- Signage manufacturing
- Metal stiffener bonding
- Trim attachment
- Georgian bars
- Electronic parts

## Technical information:

Properties	Units	Specification	Test method
Total thickness (without liner)	mm	1.0	Scapa K1
Peel adhesion	N/cm	10	AFERA 5001
Holding power	hours	72	Internal
Initial tack (steel ball) 14#:	mm	20	Internal
Temperature resistance 80°C	min	120	
Temperature resistance 120°C	min	20	
Working temperature	°C	+10 - +40	

## Color:



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.