

07755 DRYWALL JOINT TAPE

Tape structure:

Backing: Fiberglass

Adhesive: Acrylic self-adhesive latex

Product Description:

Self-adhesive high quality fiberglass tapes are used on gypsum plasterboard joints, as well as on cracks before applying filler. The tape together with filler reinforces joints and cracks.

Features:

- High strength: tensile strength ≥ 500 N (warp), ≥ 700 N (weft) for strong joint reinforcement.
- Alkali-resistant: durable when used with cement or concrete-based surfaces.
- Self-adhesive backing: coated with acrylic latex for easy application and secure bond without pre-wetting.

Technical information:

Properties	Units	Specification	Test method
Weave		Leno	
Material (Tex):	Warp: Werf:	65 99	
Density (mm):	Warp: Werf:	2.85 2.85	
Grey cloth weight	g/m ²	55	
Material weight	g/m ²	70	
Latex	%	26	
Tensile strenght: warp	N/cm	100	
Tensile strenght: weft	N/cm	140	
Adhesive time	seconds	900	
Moisture content	5%	1	



Main Application:

- Reinforcement of drywall joints before applying filler.
- Repairing surface cracks in plasterboard.
- Suitable for use on gypsum boards and over concrete substrates.

as per Q/320682SB01-1999

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.