

## 07755 Drywall joint tapes



### Description:

Self-adhesive high quality fiberglass tapes are used on gypsum plasterboard joints, as well as on cracks before applying filler. The tape together with filler reinforces joints and cracks.

Specification	Item	General code
Weave		Leno
Material (Tex):	Warp:	66
	Weft:	99
Density (mm):	Warp:	2,85
	Weft:	2,85
Standard width (mm.):	48 mm, 100 mm, 150 mm	
Standard length (m.):	20 m, 45 m, 90 m, 180 m	
Grey cloth weight (g/m <sup>2</sup> ):	55 ± 5 %	
Coating:	acrylic self-adhesive latex	
Weight (g/m <sup>2</sup> )	70 ± 5 %	
Latex	≥ 26 %	
Tensile strength (N/50mm): warp	≥ 500	
Tensile strength (N/50mm): weft	≥ 700	
Adhesive time (second)	≥ 900 s	
moisture content (5 %)	≤ 1	
Conclusion: the test methods is as per Q/320682SB01-1999		

### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.