

094500, 094125 PROTECTIVE FILM UNIVERSAL

Structure:

Backing: HDPE film

Product Description:

094500 and 094125 is a versatile HDPE film designed for temporary surface protection. This waterproof and solvent-resistant film is ideal for covering large areas and furniture, offering electrostatic adhesion.



Features:

- Protects form solvents and dust
- Suitable for large areas protection
- Electrostatic

Main Application:

- Protection of various surfaces
- Protection of large areas
- Covering areas and furniture

Technical information:

Properties	Units	Specification
Total thickness	mm	0.007
Tensile strength	N/cm	1.2
Elongation at break	%	74
Heat resistance	°C	120

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.