

0540 Fluorescent cloth tape

Construction:

Tape grade:	Fluorescent cloth tape
Mesh:	80 mesh
Carrier:	65 % (Polyester) + 35 % (Cotton) Woven Cloth with Warp & Weft
Adhesive:	Natural Rubber Base

Test report:

Total thickness (micron):	300
Peel adhesion (gf/25 mm/180°):	1,100
Tensile strength (kgf/25 mm):	14
Elongation (%):	11
Ball tack (Ball No.):	22
Holding power (mm/Hr):	0,5
* 1 kg loading on SUS plate, 25 mm x 25 mm	
Unwinding force (gf/25 mm):	900
Heat resistance (°C/min):	85/180
Weather resistance (Hrs):	8
Delamination:	No
Storage life (months):	24

Above test was performed on the condition of 23±2 °C and humidity of 65±5 % (JIS Z 0237, 1254)

All above data can be changed according to testing circumstances

Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.