

0540 FLUORESCENT GAFFER CLOTH TAPE

Tape structure:

Backing: Matt synthetic cloth (65% polyester + 35% cotton)

Adhesive: Natural rubber based UV-stabilized adhesive

Product Description:

0530 is a 300-micron professional premium-grade cloth tape. It is specially designed for heavy-duty applications where residue-free removal is required and is perfectly suitable for the arts and entertainment industry. It is fluorescent, conformable, easy to remove, and extra strong.

Features:

- Excellent adhesion properties at low and high temperatures
- Good performance on rough surfaces
- Excellent tear and unwind properties
- Clean removal for a long period

Main Application:

- Ideal for securing cables, marking stages, and temporary fixes in film, theater, and live events
- Secure bundling, fastening, and holding various items in demanding situations
- Suitable for temporary repairs and modifications where leaving no trace is essential



Technical information:

Properties	Units	Specification
Total thickness	mm	0.300
Peel adhesion	N/cm	4.7
Tensile strength	N/cm	53.7
Elongation at break	%	9.1
Heat resistance	°C/min	85/180
Application temperature	°C	-5 to +35
Temperature resistance	°C	-5 to +50

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.