

## 0777 PVC tape



### Description:

Self-adhesive tape particularly suitable for all traditional uses and for printing. The structure of PVC backing ensures excellent plasticity and rigidity mechanical features. The thick layer of adhesive gives high tack to various surfaces.

### Advantages and benefits:

- Excellent adhesion even in recycled cartons
- Excellent tack
- Long lasting adhesion
- No noise, silent unwinding
- Printable with vinyl inks
- Easy unwind and fast printability
- Once applied, ideal for storage in extreme temperature conditions and high moisture environments

### Advantages and benefits:

Backing: Unplastified clear PVC film

Adhesive: Natural rubber and hydrocarbon resins

Color: Red, yellow, green

### Technical Details:

Properties	Unit	Spec.
Backing thickness	µm	34-37 ±3.7
Total Thickness	µm	52-57 ±5.2
Peel Adhesion	N/cm	2.2 ±0.5
Tensile Strength	N/cm	47 ±12
Elongation at break	%	75 ±20
Application temperature	°C	10 to 45
Service temperature	°C	-25 to 65

### Shelf Life:

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

### Availability:

9 mm x 66 m, 12 mm x 66 m, 50 mm x 66 m

### Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.