

0777245, 077706245 PVC PACKAGING TAPE “EXTRA”

Tape structure:

Backing: PVC

Adhesive: Natural rubber

Product Description:

Self-adhesive tape particularly suitable for all traditional uses and for printing. The structure of PVC backing ensures excellent plasticity and rigidity mechanical features. The thick layer of adhesive gives high tack to various surfaces.

Features:

- Excellent adhesion even in recycled cartons
- Excellent tack
- Long lasting adhesion
- Silent and easy unwinding
- Once applied, ideal for storage in extreme temperature conditions and high moisture environments

Main Application:

Designed for carton sealing and general packaging applications, for excellent holding power and consistent performance under various temperature conditions.



Technical information:

Properties	Units	Specification	Test method
Backing thickness	mm	0.035	Internal
Total thickness	mm	0.053	Internal
Peel adhesion	N/cm	2.1	AFERA 5001/PSTC 101
Tensile strength	N/cm	47	AFERA 5004/PSTC 131
Elongation at break	%	75	AFERA 5004/PSTC 131
Application temperature	°C	+10 to +45	
Temperature resistance	°C	-25 to +65	

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.