

# 0207 MASKING TAPE “PERFECT EDGE DELICATE”

## Tape structure:

**Backing:** Japanese Washi paper

**Adhesive:** Acrylic water based

## Product Description:

0207 masking tape is designed to ensure professional finish even on the most sensitive surfaces, where any other product would cause damages. Its ultra-sensitive adhesive is designed to prevent bleed through on semi-rough surfaces as plaster walls and extremely delicate surfaces as fresh paint and wallpapers to ensure a clean and gentle removal up to 1 week after the application. It is the ideal product for indoor masking operations on common indoor surfaces up to 14 days without damaging the surface on removal. It can be precisely and reliably applied on door profiles and windows outlines exposed to UV rays up to 1 week.



## Features:

- Japanese Washi Paper
- Special ultra-delicate adhesive formula
- Sharp paint break-lines
- Resistant to moisture and most common water and solvent base paints
- Clean removal up to 1 week on extremely delicate surfaces
  - plaster, wallpapers, fresh paint
- Clean removal up to 2 weeks on common indoor surfaces
  - PVC, Glass, Wood, Aluminium
- Excellent paint anchorage

## Main Application:

- Touch-ups and finishes on fresh painted or ultra-delicate areas
- Fine Line painting indoor applications

## Technical information:

Properties	Units	Specification	Test method
Total weight	g/mm <sup>2</sup>	64	ISO 536
Total thickness	mm	0.075	Internal
Peel adhesion	N/cm	0.45	AFERA 5001/PSTC 101
Tensile strength	N/cm	30	AFERA 5004/PSTC 131
Elongation at break	%	3.5	AFERA 5004/PSTC 131

## Color:



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.