

05107/05108 Warning duct tape



Description:

Warning Duct Tape, PE laminated synthetic cloth duct tape, coated with a semipermanent synthetic rubber — resin solvent free adhesive. Its adhesive formulation resists at low temperature with excellent bonding to multiple rough and smooth surfaces. Ideal for bonding, sealing, jointing, repairing and warning-marking operations. For clean removal, long-term UV exposure not recommended.

Application:

Jointing and sealing, General repairing, Warning-marking.

Features:

- Easy tear
- · Withstand any weather condition
- · Good abrasion resistance
- Excellent conformability
- Excellent adhesion on smooth and rough surfaces
- Perfectly waterproof

Tec			

Properties	Metric	Imperial Units	Test Method
Total weight	153 g/m ²	153 g/m²	ISO 536
Total thickness	165 µm	6.5 mils	Internal
MD tensile strength	34 N/cm	19.4 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break	20 %	20 %	AFERA 5004/PSTC 131
Adhesion to steel plate	8.0 N/cm	73.1 oz/in	AFERA 5001/PSTC 101
Service temperature	-10°C / 60°C	14°F / 140°F	

Backing material: PE laminated synthetic cloth

Type of adhesive: Synthetic rubber resin - solvent free

Color: Yellow/Black, Red/White

Size: 50 mm x 33 m

Remark: Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.

april 2020 www.folsen.eu