

# 098 PRE-TAPED COVER FILM OUTDOOR

## Structure:

**Backing:** HDPE embossed film

**Tape's carrier:** Cloth masking tape

**Tape's adhesive:** Natural rubber based

## Product Description:

098 is a protective film with a self-adhesive cloth masking tape, designed for outdoor use and UV resistant for up to 14 days. This 2-in-1 product has electrostatic properties, allowing it to conform to the shape of protected surfaces. Its embossed design prevents paint from spreading and allows for quick and easy removal.



## Features:

- Protecting film + masking self-adhesive tape
- Ideal for outdoor masking
- UV resistant for 14 days
- Easy and fast removable
- Fast and easy solutions in protecting surfaces at one time
- Straight tearable by hand at vertical direction
- Statically charged HDPE film (corona treated) conforms to all surfaces
- Embossed film does not allow paint to spread

## Main Application:

- Protection for outdoor masking and plastering jobs

## Technical information:

Properties	Units	Specification
Film thickness	mm	0.009
Peel adhesion (tape)	N/cm	3.8
Tensile strength (tape)	N/cm	55.7
Elongation at break (tape)	%	9
Heat resistance (tape)	°C	40
UV resistance	days	14

## Color:



## SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

## IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.