

## 06825057 Anti slip tape



### Description:

Water resistant anti-slip tape meant to protect from slip-accidents in bathtubs and showers. This tape can be used also outdoors.

### Construction:

PEVA coated with solvent acrylic adhesive.

Thickness of carrier is 0.75mm, total thickness 0.85mm

### Technical Details:

Properties	Value	Unit	Test method
Adhesion	0.248±0.02	G/cm	PSTC-4
Tensile	2.6±0.5	Kgs/cms	PSTC-31
Tear Resistance	5600±100	G	PSTC-39
Elongation at break	110±15	%	PSTC-31
Temperature range	-20 ~ +80	°C	/
Resistance to water	10	months	PSTC-35
Resistance to chemicals	8	months	PSTC-35
Resistance to motor oil	Excellent	/	PSTC-35

### Application requirements:

Temperature: between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

### Storage and shelf life:

Clean and dry in a well ventilated area, preferably at a temperature between 10 °C and 30 °C. Stored under these conditions shelf life will be a minimum of 12 months.

### IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.