

0945018, 0941218, 0942018 Professional protective film



Description:

Highly durable protective film for protection of various surfaces in various works, including professional construction, DIY and automotive industry.

- Electrostatic
- Flexible and durable material
- Protection from dust, dirt, paints and solvents
- Resistant to spray booth temperatures and infrared drying
- Resistant to compressed air, can be blown dry

Specifications:

LDPE film	
Thickness (µm)	18
Color	White
Sizes and packaging way	4 m x 5 (20m ²) flat packed 2 m x 12 m (24m ²) in a roll, perforated every 1 meter 2 m x 20 m (40m ²) in a roll, perforated every 1 meter
Temperature resistance	10 °C — 100 °C (Working range in spray booth)

Remark:

Above figures are for reference and cannot be treated as warranties. Customers are advised to test the material to determine the suitability against intended applications.

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture.