

0945018, 0941218, 0942018 PROTECTIVE FILM PROFESSIONAL

Structure:

Backing: LDPE film

Product Description:

The 18 microns protective film is designed for reliable protection of various surfaces during construction and renovation works. This film is made of durable LDPE (low-density polyethylene) and offers increased resistance to mechanical damage and exposure to solvents. Thanks to its electrostatic properties and high elasticity, the film is easy to apply and provides effective coverage of large areas.

Features:

- Provides reliable protection against various chemicals and solvents
- Clings to surfaces without additional fixing agents.
- Stretches without tearing, ensuring durability during application
- Ideal for protecting wide areas such as floors, furniture, and walls
- Resistant to high temperature treatment in paint boxes
- Rolls are perforated at every 1 meter for handy usage

Technical information:

Properties	Units	Specification
Total thickness	mm	0.018
Tensile strength	N/cm	3.4
Elongation at break	%	250/560
Heat resistance	°C	140

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.

