

03012 DOUBLE-SIDED PE FOAM MOUNTING TAPE

Tape structure:

Backing: PE foam

Adhesive: Natural rubber

Release liner: Glassline paper

Product Description:

Cross-linked polyethylene (PE) foam is coated with solvent based natural rubber adhesive on both sides. For indoor use and secure bonding for heavy-duty mounting.

Features:

- Quick stick for efficient operation
- Good Shear Strength for secure bonding
- Flexible Foam material to provide comfortable mating to contour surface

Technical information:

Properties	Units	Specification	Test method
Total thickness (without liner)	mm	1.0	Internal
Peel adhesion	N/cm	7.8	PSTC-3
Shear Strength	hours	24	2kg loading on 25mm x 25mm sandwich 2 stainless steel plates at 25 °C
Working temperature	%	-10 - +50	Internal



Main Application:

- Especially designed for heavy duty hangers holding.
- Suits perfectly for mounting and joining of nameplates, plastic trim, signs and emblems, as well as for window glazing.

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.