

097 PERFECT EDGE PRE-TAPED DROP FILM

Structure:

Backing: HDPE film

Tape's carrier: Japanese washi paper, waterproof

Tape's adhesive: Acrylic

Product Description:

Protective film with self-adhesive masking tape. Ideally suitable for protecting of different surfaces. The product has a strong but thin carrier which provides extra strength to the product and guarantees ultra sharp paint lines at the same time. This time saving and compact 2-in-1 masking concept can be used for temporary protection of doors, windows, windowsills, radiators and furniture during painting and plastering. The tape is suitable for masking on fragile and delicate surfaces during extended periods of time. Depending on the type of surface the traceless removability can be guaranteed up to 6 months. Product is UV resistant outdoors for up to 3 months



Features:

- 2-in-1 masking solution
- Ultra sharp paint lines
- Surface-safe adhesion
- UV resistance

Main Application:

- Protection for indoor and outdoor supersharp masking jobs

Technical information:

| Properties | Units | Specification |
|----------------------------|-------|---------------|
| Film thickness | mm | 0.008 |
| Peel adhesion (tape) | N/cm | 1.4 |
| Tensile strength (tape) | N/cm | 30 |
| Elongation at break (tape) | % | 5 |
| Heat resistance (tape) | °C | 90 |
| UV resistance (tape) | days | 90 |

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.